

IMPERIAL

LUXURY EMULSION

Pro-Tech Imperial Luxury Emulsion with colour stay is a water-based, 100% acrylic, anti algal, high performance exterior wall finish.

BENEFITS

Pro-Tech Imperial Luxury Emulsion offers advanced protection and lasting beauty. The Green Assure promise ensures eco-friendly formulation with minimal chemicals and low odor. Its Teflon Surface Protector enhances durability, making walls resistant to tough stains like turmeric and ink. Additionally, the Anti-Bacterial and Anti-Fungal Shield prevents fungal growth and eliminates 99.8% of microorganisms, meeting Japanese Industrial Standards.



DIRECTIONS FOR USE

PLASTER

New masonry surfaces must be fully cured before painting. A curing period of 28 days is recommended for best results.

CLEANING

Ensure the surface is free from loose paint, dust, or grease. Remove any fungus, algae, or moss using a wire brush and water.

FILLING CRACKS

For cracks up to 3mm, use Pro-Tech Crack Fill Powder for effective sealing.

FILLING HOLES & DENTS

For dents and holes, use Tiger Gold Acrylic Wall Putty or a 1:3 mixture of white cement and fine sand.

POST-PAINTING CARE

- Act quickly-remove stains immediately to prevent permanent marks.
- Use a clean, dry cloth or duster to remove dirt, always wiping from top to bottom to avoid smudging.
- For common household stains like pencil marks, tea, coffee, or crayon, use a 5% soap detergent solution and a sponge.
- For tough stains such as turmeric or sketch pen marks, use a mild detergent solution for effective cleaning.

SAFETY FEATURES

- Kindly refer to the MSDS for Pro-Tech Imperial Luxury Emulsion which gives detailed information on safety measures while handling the paint, which is available on request.
- Store the container with the lid tightly closed in an upright position, in a cool, dry place. Keep out of reach of children and away from eatables.
- If swallowed, it can be harmful. In case of ingestion seek immediate medical attention.
- Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- In case of skin contact immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
- Do not breathe vapor or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.
- Do not pour leftover paint down the drain or in water courses. In the event of spills, contain spillage using sand or earth.
- No added Lead, Mercury or Chromium compounds.
- Left-over paint/drums should not be disposed in soil/drains. Consumers should consult a local recycling agency for proper disposal of paint/drums.

Smooth Finish Easy Clean



HIGH UV
RESISTANCE



HIGH
DURATION



DILUTION 10-20%
WITH SYNTHETIC THINNER

Available Packs
20, 10, 4, 1 Ltr

Coverage
100-120 Sqft

Shelf Life
18 Months

